



TWIN CHARGE VITRIFIED TILES
600X600MM



NAOMI 600x600mm



ZELENA 600x600mm



UDELE 600x600mm



LINETTE 600x600mm



PACKAGING DETAIL FOR 600x600MM POLISHED VITRIFIED TILES

Nominal Size	Thickness	No. Of Tiles per carton	Weight	Coverage area per Carton
600x600mm	8.8mm	4 Pcs	26.50 Kg. / Box (Approx)	1.44 Sq. Mtr / 15.50 Sq. ft.

TECHNICAL SPECIFICATION FOR 600x600MM POLISHED VITRIFIED TILES


Characteristics	Requirement as per IS 15622 :2017 E ≤ 0.08 Group B I a	Requirement as per ISO 13006 ≤ 0.5% Group B I a	Our Values	Test Method
Dimension & Surface Quality				
Length & Width	± 0.10%	± 0.5%	± 0.10%	IS 13630 Part 1/ ISO 10545-2
Thickness	± 5.00%	± 5.00%	± 4.0%	
Straightness of Side	± 0.10%	± 0.50%	± 0.10%	
Rectangularity	± 0.10%	± 0.60%	± 0.10%	
Surface Flatness				
Center Curvature (%) (Max. Dev.)	± 0.50%	± 0.50%	± 0.2 %	
Edge Curvature (%) (Max. Dev.)	± 0.50%	± 0.50%	± 0.2 %	
Corner Warpage (%) (Max. Dev.)	± 0.50%	± 0.50%	± 0.2 %	
Surface Quality	Min. 95 % of tiles will be free from visible defects	Min. 95 % of tiles will be free from visible defects	Min. 95 % of tiles will be free from visible defects	
Physical Properties				
Water Absorption	Average ≤ 0.08%, Individual Max.1.0 %	Av ≤ 0.5 %, Individual 0.6% max	Max. < 0.08%	IS 13630 Part 2/ ISO 10545-3
Modulus of Rupture [N/mm ²]	Av 35, Individual 32 min	Av 35, Individual 32 min	Avg.40, Individual 38 Min	IS 13630 Part 6/ISO 10545-4
Breaking Strength in N	1300	Min.1300	Min 1500 N	
Moisture Expansion in mm/m	0.02	Test method available	0.02	IS 13630 Part 3/ISO-10545-10
Scratch Hardness of Surface (Mohs)	Min 5	N.A	Min 5	IS 13630 Part 13
Coefficient of Linear Thermal Expansion from Ambient Temperature to 100° C	6 × 10 ⁻⁶ K ⁻¹ Max	Test Method Available	Max 6 × 10 ⁻⁶ K ⁻¹ Max	IS 13630 Part 4/ ISO 10545-8
Thermal Shock Resistance	10 Cycle Min	Required	10 Cycle Passed	IS 13630 Part 5/ISO-10545-9
Crazing Resistance	4 Cycle @ 7.5 bar Min	N.A	N.A.	IS 13630 Part 9/ISO 10545-11
Impact Resistance as Co-efficient of Restitution (COR)	0.55 Min	Test Method Available	0.75-0.95	IS 13630 Part 14/ISO 10545-5
Deep Abrasion Resistance	140,Max	Max.175	Max.100	IS 13630 PART 12/ISO 10454-6
Frost Resistance	Required	Required	100 Cycle Passed	IS 13630 Part 10/ISO 10545-12
Chemical Resistance (Unglazed Tiles)				
Stain Resistance	Min Class 2	Manufacturer to State The Class	Min Class 2	IS 13630 Part 8/ISO 10545-14
Resistance to Household chemicals	Min Class AA	Min Class UB	Min Class AA	
Resistance to acids and alkalis (with exception of hydrofluoric acid and its compounds)	Required if Agreed	Test Method Available	Min Class A	IS 13630 Part 7/ISO 10545-13

The reproduction of tiles in this catalogue is restricted to four color printing only and tiles are not in relative sizes, therefore customers are advised to see the physical sample before placing the order. "Technical Specification" for Somany wall & floor tiles are applicable only for premium quality tiles. Please inspect all tiles prior to installation. Company will not entertain complaints once tiles are laid/fixed. Complaints will not be entertained for Borders, Highlighters & Motifs.

SOMANY

Somany Ceramics Limited : Noida: F-36, Sector-6; Ph.: 0120-4627900.
Ahmedabad: Office no. 7-14, 4th Floor, Aggarwal Mall, Opp. Sola Bhagwan Vidyapeeth, S.G. Road, Sola, Ph.: 079-66042500 to 599
Registered office: 2, Red Cross Place, Kolkata - 700001; Ph.(033) 22487406/5913
www.somanyceramics.com | e-mail marketing@somanyceramics.com

Toll Free No. 1800-103-0004 (Timing-10:00am to 6:30pm; Mon-Fri)



Visit us at:

www.somanyceramics.com



Find us at:

www.facebook.com/SomanyCeramic



Find us at:

www.twitter.com/SomanyCeramic



Available on the



Google play

PVT / LEAFLET / NOV-2019

600x600MM



VITRO




ZAMEEN SE JUDAY




TWIN CHARGE VITRIFIED TILES 600X600MM

Powered by
**TWIN
CHARGE**
PRINT TECHNOLOGY



Somany, the name synonymous with innovation and style has been the pioneer of Twin Charge technology. Due to its distinct feature and cutting edge printing, it has now become Industry benchmark in India as well as globally. These tiles not only come with great designs but are highly durable and can withstand heavy traffic areas. These tiles are epitome of whiteness and now the most preferred choice of customers having an eye for design.




TWIN CHARGE VITRIFIED TILES 600X600MM



BRITANY 600x600mm



MELODY 60x600mm



CHERYL 600x600mm



HALEY 60x600mm

